

KENWOOD

Listen to the Future

NEXEDGE®

NX-200S/300S

NEXEDGE® VHF/UHF Digital & FM Portable Radios

NXDN®

FleetSync® by KENWOOD



● GENERAL FEATURES

- 5 W (136-174 MHz) Models
- 5 W (400-470 MHz) Models
- Meets ETSI EN Standards
- 64 CH-GID / 4 Zones
- Transmit / Busy / Call Alert / Warn LED
- On / Off Volume Knob
- 16-Position Mechanical Selector
- 2 Side PF Keys
- Emergency / AUX Key
- 500 mW Speaker Audio
- Emergency Call Features
- Lone Worker
- KMC-47GPS Speaker Mic Option
- KPG-111D Windows® FPU*¹
- Flash Firmware Upgrading
- MIL-STD-810 C/D/E/F/G
- IP54/55 Water & Dust Intrusion
- PC Serial Interface
- VGS-1 Voice Guide / GPS Data Storage Option
- Transparent Data Mode*²

● DIGITAL – GENERAL

- NXDN® Digital Air Interface
- AMBE+2™ VOCODER
- 6.25 & 12.5 kHz Channels
- Over-the-Air Alias (TX)
- Emergency Call
- All Group Call
- Status Messaging*² *³
- Remote Stun / Kill*²
- Remote Check*²
- Short & Long Data Messages*²
- GPS Location with Voice*²
- NXDN® Scrambler Included

● DIGITAL – CONVENTIONAL MODE

- 64 Radio Access Numbers (RAN)
- Individual & Group Selective Call*⁴
- Mixed FM / Digital Operation
- Conventional IP Networks
- Site Roaming

● DIGITAL – TRUNKING MODE

- Individual Private Call (RX / Talkback only)
- Group Call & Broadcast Call
- Transmission Trunked Mode*⁵
- Message Trunked Mode*⁵
- Call Queuing with Priority*⁵
- Late Entry (UID & GID)*⁵
- 4 Priority Monitor ID's*⁵
- Remote Group Add*²
- Failsaft Mode*⁵

● MULTI-SITE IP NETWORK COMPATIBLE

- 60,000 GIDs / UIDs
- Wide Area Group Call
- Auto Roaming Registration
- Group Registration

● SCAN

- Single / Multi-Zone Scan / List Scan
- Dual Priority Scan (Conventional)

● FM MODES – GENERAL

- 25, 20 & 12.5 kHz Channels
- FleetSync® / II*⁴
- DTMF Encode / Decode*⁴
- Voice Inversion Scrambler
- Analogue Scrambler Board Capability

● FM CONVENTIONAL ZONES

- QT / DQT / Two-Tone*³
- 5-Tone Encode / Decode*³
- Call Key 1-6
- Voting

● FM LTR® TRUNKED ZONES

- Kenwood LTR® Features

● FleetSync® / II (FM)*⁴

- PTT ID Digital ANI
- Selective Call & Group Call*⁴
- Status Messaging*² *³
- Emergency Status
- Short Text Messages*²

● MDC-1200

- PTT ID Digital ANI
- Caller ID Display
- Emergency Status
- Radio Check
- Radio Inhibit

¹ The KPG-111D must be version 2.00 or later.

² Requires NX subscriber unit PC Serial Interface compatible software application (e.g. Kenwood AVL & Dispatch Messaging software) or hardware (e.g. console).

³ Pre-programmed key operation

⁴ Some screen/key-based functions are not available on the NX-200S/300S.

⁵ These trunked features are primarily system programming and operational dependent. Priority monitor also requires NX subscriber settings.

Options

<p>■ KNB-47L Li-Ion Battery (1950mAh)</p> 	<p>■ KMC-41 Heavy Duty Speaker Microphone with Noise-cancelling</p> 	<p>■ KVC-21 Vehicular Charger</p> 	<p>■ KHS-14 Lightweight Single Muff Headset</p> 
<p>■ KNB-48L Li-Ion Battery (2550mAh)</p> 	<p>■ KMC-42W IP67 Heavy Duty Speaker Microphone with Noise-cancelling</p> 	<p>■ KEP-1 Heavy Duty Earphone</p> 	<p>■ KHS-15-OH Heavy Duty Over-the-Head Headset</p> 
<p>■ KSC-32 Tri-Chemistry Rapid Rate Charger</p> 	<p>■ KMC-47GPS GPS Speaker Microphone</p> 	<p>■ KHS-11BL 2-Wire Palm Mic with Earphone</p> 	<p>■ KRA-22/23 VHF/UHF Helical Antenna</p> 
<p>■ KSC-326 Multiple Charger</p> 	<p>■ VGS-1 Voice Guide and Storage Unit</p> 	<p>■ KHS-12BL 3-Wire Mini Lapel Mic with Earphone</p> 	<p>■ KRA-26/27 VHF Helical Antenna UHF Whip Antenna</p> 
			<p>■ KBH-11 Belt Clip</p> 

All accessories and options may not be available in all markets. Contact an authorized Kenwood dealer for details and complete list of all accessories and options.

Main Specifications

	NX-200S	NX-300S
GENERAL		
Frequency Range	136-174 MHz	400-470 MHz
Number of Channels	64	
Zones	4	
Max. Channels per Zone	16	
Channel Spacing	Analogue Digital	12.5 / 20 / 25 kHz 6.25 / 12.5 kHz
Operating Voltage	7.5 V DC ± 20%	
Battery Life (with KNB-48L)	5-5-90 10-10-80	More than 14.5 hours More than 9.0 hours
Operating Temperature Range	-30° C to +60° C	
Frequency Stability	± 2.0 ppm	± 1.0 ppm
Antenna Impedance	50 Ω	
Dimensions (W x H x D)	Projections not included	
	Radio only	58 x 128.3 x 41.7 mm
	with KNB-47L	58 x 128.3 x 41.7 mm
	with KNB-48L	58 x 128.3 x 49.1 mm
Weight (net)	Radio only	255 g
	with KNB-47L	370 g
	with KNB-48L	400 g
Applicable Standards	ETSI R & TTE	EN 300 086, EN 300 113, EN 300 219, EN 301 489, EN 301 166
	ETSI Safety	EN 60065, EN 60950-1, EN 60215

FleetSync® is a registered trademark of Kenwood Corporation.
LTR® is a registered trademark of Transcript International.
AMBE+2™ is a trademark of Digital Voice Systems Inc.
Windows® is a registered trademark of Microsoft Corporation.
NXDN® is a registered trademark of Kenwood Corporation and Icom Inc.
NEXEDGE® is a registered trademark of Kenwood Corporation.

	NX-200S	NX-300S
RECEIVER		
Sensitivity (Analogue)	EIA 12dB SINAD	0.28 µV / 0.28 µV / 0.32 µV
(25kHz / 20kHz / 12.5kHz)	EN 20dB SINAD	-3 dB µV (0.35 µV) / -3 dB µV (0.35 µV) / -1 dB µV (0.45 µV)
Sensitivity (Digital)	3% BER	0.32 µV / 0.25 µV
(12.5kHz / 6.25kHz)	1% BER	-1 dB µV (0.45 µV) / -4 dB µV (0.32 µV)
Adjacent Channel Selectivity (Analogue)	(25kHz / 20kHz / 12.5kHz)	76 dB / 74 dB / 68 dB
Intermodulation (Analogue)		65 dB
Spurious Response Rejection (Analogue)		75 dB
Audio Distortion		Less than 3%
Audio Output		500 mW / 8 Ω
TRANSMITTER		
RF Power Output	High / Low	5 W / 1 W
Modulation Limiting (Analogue)		± 5.0 kHz at 25 kHz ± 4.0 kHz at 20 kHz ± 2.5 kHz at 12.5 kHz
Spurious Emission		-36 dBm ≤ 1 GHz, -30 dBm > 1 GHz
FM Noise (EIA)	(Analogue, 25 kHz / 20 kHz / 12.5 kHz)	45 dB / 45 dB / 40 dB
Modulation Distortion		Less than 3%
Microphone Impedance		1.8 kΩ
Modulation		16K0F3E, 14K0F3E, 14K0F2D, 12K0F2D, 8K50F3E, 7K50F2D, 8K30F1E, 8K30F1D, 8K30F7W, 4K00F1E, 4K00F1D, 4K00F7W, 4K00F2D

Analogue measurements made per EN Standards or TIA/EIA 603 and specifications shown are typical. Kenwood reserves the right to change specifications without prior notice or obligation.

Applicable MIL-STD & IP

MIL Standard	MIL 810C Methods/Procedures	MIL 810D Methods/Procedures	MIL 810E Methods/Procedures	MIL 810F Methods/Procedures	MIL 810G Methods/Procedures
Low Pressure	500.1/Procedure I	500.2/Procedure I, II	500.3/Procedure I, II	500.4/Procedure I, II	500.5/Procedure I, II
High Temperature	501.1/Procedure I, II	501.2/Procedure I, II	501.3/Procedure I, II	501.4/Procedure I, II	501.5/Procedure I, II
Low Temperature	502.1/Procedure I	502.2/Procedure I, II	502.3/Procedure I, II	502.4/Procedure I, II	502.5/Procedure I, II
Temperature Shock	503.1/Procedure I	503.2/Procedure I	503.3/Procedure I	503.4/Procedure I, II	503.5/Procedure I
Solar Radiation	505.1/Procedure I	505.2/Procedure I	505.3/Procedure I	505.4/Procedure I	505.5/Procedure I
Rain	506.1/Procedure I, II	506.2/Procedure I, II	506.3/Procedure I, II	506.4/Procedure I, III	506.5/Procedure I, III
Humidity	507.1/Procedure I, II	507.2/Procedure II, III	507.3/Procedure II, III	507.4	507.5/Procedure II
Salt Fog	509.1/Procedure I	509.2/Procedure I	509.3/Procedure I	509.4	509.5
Dust	510.1/Procedure I	510.2/Procedure I	510.3/Procedure I	510.4/Procedure I, III	510.5/Procedure I
Vibration	514.2/Procedure VIII, X	514.3/Procedure I	514.4/Procedure I	514.5/Procedure I	514.6/Procedure I
Shock	516.2/Procedure I, II, V	516.3/Procedure I, IV	516.4/Procedure I, IV	516.5/Procedure I, IV	516.6/Procedure I, IV
International Protection Standard					
Dust & Water Protection	IP54/55				

Listen to the Future

Kenwood has always connected with people through sound. Now we want to expand the world of sound in ways that only Kenwood can, listening to our customers and to the pulse of the coming age as we head toward a future of shared discovery, inspiration and enjoyment.

Kenwood Electronics UK Limited

Kenwood House, Dwight Road, Watford, Herts, WD18 9EB, United Kingdom

www.kenwood-electronics.co.uk

http://hexedge.kenwood.com

