PT68+

Conventional Portable Radio

Kiricom

PT68+

Main Functions:

- **Multiple Scanning Function**
  Multi scanning function offers wide applicability.
- **RF Power Selectable**
  High/Low power is selectable.
- **CTCSS**
  Built-in CTCSS encoder/decoder can activate repeater and selective calls.
- **Menu**
  You can select CTCSS, high/low power, and scanning channel by menu.
- **Keypad Lock**
  Keypad lock can prevent misoperation.
- **VOX**
  Allows hands free communication.
- **Display**
  6 Character alphanumeric LCD display.

PT68+

KIRICOM Your smart choice

SPECIFICATIONS

General

Frequence	66 ~ 88 MHz
Number of Channels	256
Channel Spacing	25 kHz/12.5 kHz
Operating Temperature	-25°C ~+55°C
Antenna Impedance	50Ω
Microphone Impedance	2k Ω
Frequency Stability	±2.5ppm
Battery(Standard)	Li-Ion 1700mAh
Dimensions(W x H x D)	56mm x 120mm x 35mm
Weight	305g(with battery and antenna)

Receiver

Sensitivity (12dB SINAD)	0.25μ V(W)/0.28μ V(N)
Operating Band Width	±7KHz(W)V/±3.5KHz(N)
Adjacent Channel Selectivity	⩾70dB(W)/60dB(N)
Intermodulation Reject Ratio	⩾65dB
Spurious Response Reject Ratio	⩾70dB(W)/⩾60dB(N)
AF Output Power	500mW (distortion less than 5%)

Transmitter

RF Power	5W/1W
Spurious and Harmonics	⩽-70 dB
FM Noise(300~3000Hz)	⩽-40dB(W)/⩽-35dB(N)
FM Distortion(300~3000Hz)	⩽5%
Maximum Frequency Deviation	±5kHz(W)/ ±2.5kHz(N)

Standard Accessories

KBC-28L
Desktop Charger

KB-17L
Battery Pack

Antenna

Hand Strap

Optional Accessories

KME-62B
Earpiece-Mic

KME-62A
Speaker-Mic